

80hp-125hp SK Series Wheeled Tractor +



PRODUCT FEATURES

- ◆ SK series wheeled tractor equipped with YTO engine with advanced European technology is able to meet different working condition and save fuel.
- ◆ The right side-mounted console and flat deck which make the driver easy and handy to operate the tractor.
- ◆ Independent dry dual-stage clutch guarantee you a safe and high-efficiency operation process.
- ◆ By adopting European technology and design philosophy, the SK series tractors can offer 16 F+ 8R, 8F+ 4R and 8F+8R three kinds of transmissions for choice to satisfy various agronomic requirements. Among the three kinds of transmissions, 8F+4R transmission is the standard configuration and other configurations are options.
- ◆ The standard hydraulic system features height control, draft control and hydraulic high-pressure into the earth model. And the draft control and position control are optional device.
- ◆ The electrical system adopts waterproof design to avoid damage during the rainy season.
- ◆ For the reliable, safe and easy driving operation, it is equipped with oil immersed disc brake and hydraulic power steering system.

TECHNICAL PARAMETERS

Product Model	800/804	900/904	1000/1004	1100/1104	1204B	1254B	
Drive Type	4 × 2 / 4 × 4						
overall dimension (mm)	Length	4250	4250	4250	4250	4700	4700
	Width	2070	2070	2070	2070	2070	2070
	Height (with Cab)	2720 (2WD) / 2830 (4WD)			3100 (to top of filter)		
	Height (with sunroof)	3000 (to top of sunroof)					
Mi. Ground Clearance(mm)	450(to bracket of the fuel tank)/380(to bottom of front axle)						
Wheel Tread(mm)	Front	(1550 as factory set)、1650、1750、1850 (2WD) / (1660 as factory set) 、1760、1860、2000 (4WD)					
	Rear	(1620 as factory set) 、1710、1820、1910、2020					
Structure Weight (kg)	With Cab	3400/3800	3400/3800	3400/3800	3400/3800	4270	
	With sunroof	3150/3550	3150/3550	3150/3550	3150/3550	4110	
Counter weight(kg)	Front 前	220 (2WD) / 400 (4WD)					
	Rear 后	300					
Engine	Model	LR4B5-23	LR4M5-23	LR4V5-23	LR4B3Z-23(Option LR6B3-23)	LR6B5-23	LR6M5-23
	Number of Cylinder	4	4	4	4(6)	6	6
	Bore x stroke	108 × 135	110 × 135	115 × 135	108 × 125	108 × 135	110 × 135
	Rated power(kW)	59	66.2	73.5	81	88.2	92
	Rated Speed	2300					
Max traction force (kN)	15.6/16.9	17.6/19.1	18.7/20.3	19.8/22.3	26.8	26.8	
Max PTO power (KW)	50	56.3	62.5	68.9	78.2	78.2	
PTO Rotating Speed(r/min)	Standard:540/1000; Option: 540/760;760/850;760/1000						
Tyre	Front	6.5-20 (2WD) / 11.2-24 (4WD)					
	Rear	16.9-34					
Gearbox	Standard:8F+4R ; Option1 Creeper: 16F+8R;Option shuttle:8F+8R						
Speed (km/h)	2.31 ~ 34.67						

NOTE: The company reserves absolute rights to modify the specifications of machine and components therein without any prior notice.

K&F International Co.,Ltd

Address: Room 602, Building 3-2, Luoyang National University Science Park, China(Henan) PFTZ

Postal Code: 471001.

Tel: +86-379-6999 7655.

Mob: +86-136 08666116.

Fax: +86-379-6999 7655.

Email: kf@kfinternational.com.cn

Web Site:

Http://www.kfinternational.com.cn

Http://www.kf-international.com

